

# TRT TUBELESS RIM TAPING



Automatic stick of stretch tape  
for tubeless wheels

## SPECIFICATIONS

Range :	24" to 28" wheels
Production capacity :	60* to 120 W/hour depending on setting
Working air pressure :	6 bars minimum
Air consumption :	5 liters/min
Electrical connection :	220V
Power consumption :	200/1000 * VA
Sound level :	80 dB
Weight :	145 kg
Size :	Size : 1,1 x 0,8 x 1,65 m
Safety mark :	CE

\*With heating option

## MAIN FEATURES

- **Adjustable tape stretching force**
- Adjustable rim revolutions
- Wheel library for settings recall
- Rim tape width : up to 42mm
- Tape roller up to 250mm diam

## OPTION

- Tape Heating option
- Automatic valve hole tape punching

With more than 50 years of experience, **Mach1 Machinery** has given way to **BikeBotix** to offer you an even more comprehensive offer.



**WHEEL BUILDING**



**RIM MANUFACTURING**



**BIKE ASSEMBLY**



**DATA MANAGEMENT**



**BIKE TOOLS**

**A global presence  
French know-how since 1971**



Alongside expert and highly qualified development and customer service team 5 areas of expertise.

Proud to be a major player and a reference partner, BikeBotix exports worldwide solutions based on 4 fundamentals:

**INNOVATION, PERFORMANCE, RELIABILITY and FLEXIBILITY.**

**BIKEBOTIX**  
SOLUTIONS IN MOTION

294 route des grands bois  
74370 Villaz France  
+33 450 220 639  
machines@bikebotix.com  
www.bikebotix.com